

PT 2A 50mm/2in Centrifugal Trash Pump

Item Number: 0009095

PT 2A

High performance centrifugal trash pumps designed to keep your jobsite dry

>> Wacker Neuson's centrifugal trash pumps have proven themselves on jobsites around the world. With an optimized impeller design and built-in contractor friendly features, this line of trash pumps has redefined the quality and durability standards of self-priming centrifugal trash pumps. Which pump must be selected – Calculation examples Pumps performance curves – overview <<



Additional Advantages

- Self-priming high performance pump capable of handling solids up to 1 inch, ideal for most jobsites that require fast dewatering on command.
- Hardened ductile iron impeller and volute with a patented volute insert provides a rugged, easy to maintain pump that will stay on the job longer.
- High strength, lightweight aluminum housing, compact with easy access, allows extra years of trouble-free operation.
- Radial flow design produces high volume and head for superior pump performance.
- Quality components such as carbon ceramic mechanical seals for extra long life.

| Description | Metric | Imperial |
|---------------------------------------|--|-----------------------|
| Operating weight | 43 kg | 96 lb |
| Shipping weight (including packaging) | 49 kg | 109 lb |
| Shipping size | 565 x 480 x 540 mm | 22.3 x 18.9 x 21.3 in |
| Max. head | 32 m | 106 ft |
| Max. discharge | 795 l/min | 210 US gpm |
| Max. suction lift | 7,6 m | 25 ft |
| Solid size capacity | 25 mm | 1 in |
| Engine Type | air-cooled, 4-cycle, single cylinder, gasoline engine Honda | |
| Displacement | 163 cm ³ | 9.9 in ³ |
| Max. Rated Power at Rated Speed* | 3.6 kW at 3600 rpm | 4.8 hp at 3600 rpm |
| Operating speed | 3.500 1/min | 3,500 rpm |
| Power Rating Specification | SAE J1349 | SAE J1349 |
| Fuel capacity | 3,6 l | 3.8 US qt |
| Max. fuel consumption | 1,7 l/h | 1.9 US qt/h |
| Suction & discharge diameter | 50 mm | 2 in |
| Length x width x height | 550 x 465 x 500 mm | 21.7 x 18.3 x 19.6 in |

Standard Package - PT 2A

Above package includes strainer, t-bolt clamp, operator's manual and parts book.

Please refer to our [Price List and Ordering Guide](#) for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Friday, November 12, 2010

